## **Pneumatic Quick-Disconnect Lockout**



- Isolates pneumatic energy without the expense and inconvenience of installing in-line lockout valves
- Device is applied to the male fitting, isolating equipment from all compressed air sources
- Accommodates the majority of 1/4", 3/8", 1/2" male fittings
- Hole in center of device allows for permanent storage on an air hose and a loop on the side can be used to hang the hose and lockout device
- Lockout using a padlock with 1/4" or 9/32" shackle

Catalog Number 64221/pkg of 1 65645/pkg of 6

## **PRINZING Electrical/Pneumatic Plug Lockout**





- Accommodates a large variety of electrical plugs up to 31/2" in diameter and 5" in length as well as male air hose connectors
- Holes accommodate electrical cord or "necked down" pneumatic male fittings commonly attached to compressed air hose
- Works on 110V, 220V & 550V plugs
- Made of Polystyrene material

Catalog Number	Description
PL027E	Electrical/Pneumatic Plug LO

## **SMC Air Line Regulator Lockout**



- Enables regulator to be locked in the on, off or throttled position
- Easy installation: remove snap cap, install lockout on regulator rod, snap replacement cap on regulator.
- Comes with lockout, cap and allen wrench

Catalog No.	Description
64539	Lockout for Miniature SMC Models
	AR2000 / NAR2000
64540	Lockout for Intermediate SMC Models
	AR3000 / NAR3000